

NEW FEATURES ON THE Davenport HP Machine

DAVENPORTHP
HIGH PRECISION

<http://davenportmachine.com>
167 Ames Street Rochester NY 14611
Phone-585.235.4545 Fax - 585.235.7997

- Controls package mounted and pre-wired to machine to enable faster startup at the customer's facility. The ability to move the machine as one unit without disconnecting the controls package (as in the previous package) reduces the amount of time required to move and power up the machine.
- The coolant pump is located off the floor and mounted to the machine pan, tucked under the stock reel cover to enable storage of stock along side of stock carrier. All controls and pumps are located off of floor for ease of cleaning.
- The Lube pumps are located at a serviceable height for easy filling and maintenance. A drip pan is located below the pumps to catch any spills while filling the tanks.
- The Machine Interface (MMI) is located at a user friendly height for ease of control and function. The MMI is mounted on a pendant system that is able to be swung around the machine to be used from the front, end, or back of the machine.
- The Emergency Stops are located at multiple locations around the machine to assist the operators, maintenance, and setup personnel in removing output power (both electrical and pneumatic) while working on the machine.
- The pneumatics package has been updated to include improved filtering and control through individually adjustable regulated valves. Improved coolant filtering reduces the cleaning frequency required on the filter screens.
- All lube and air gauges are located outside of machine enclosure for ease of viewing.
- Additional window located near the 5th position burring attachment for easier viewing while the machine is running. This enables the operator to monitor machine function without opening the safety interlocked doors.

